Pobrano z mamadecor.pl

# Ego new

**Linear system composed of extruded aluminum profile and lighting elements with magnetic fixing and mechanical safety lock. The system is available in black, white or satin brass color for ceiling, suspended or recessed installation. The profile section is 26 mm wide and 27 mm or 52 mm high. Available in two lengths: 1000 mm and 2000 mm. Possibility of assembly with di□erent source modules which can be combined following the desired disposition and can be modified when needed: TRACK SINGLE or DOUBLE modules for a spot illumination, ACCENT module with glare control (UGR < 19), PENDANT TUBE module for a localized illumination and WIDE and WALL WASHER modules for a di□used and uniform illumination. Integrated LED with color temperature of 3000k and CRI 90; IP20 protection, insulation class III, 48 Vdc power source,; LED useful life 50.000 h L70B5. The system is also available with DALI dimmable version. Ideal for lighting small and in large environments where great flexibility and color rendering is required, such as MUSEUMS, COMMERCIAL, RESIDENTIAL and RETAIL spaces.**

PRO High-tech product with high quality materials, intended for professional use.

UGR Product with UGR <19 (Accent, Pendant).

| | |
|---|---|
| Source | LED COB / SMD |
| Driver included | No |
| Drivers available | On/Off |
| Control | On/Off / DALI |
| MacAdam | SDCM 3 |
| CCT | 3000K |
| CRI | ²90 |
| UGR | <19 (Accent, Pendant) |
| LED life | 50.000h |
| Insulation class | III |
| IP | 20 |
| Material | Aluminum |
| Warranty | 5 years |