Pobrano z mamadecor.pl

Path

rev. 24-08-2022

General info

Outdoor - Floor

Outdoor ground mounted bollard with integrated LED sources and direct light emission

Ean	8021696250816
Item	PATH PT ROUND 4000K
Installation	Floor
Guarantee	5 years
Gross weight	2.39 kg
Volume	0.023826 m^3

Technical info

Net weight	1.9 kg
Insulation class	I
Protection index	IP65
Operating temperature	-15° ~ +45 °C
Dimmer	Non-dimmable, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included
	YES (by qualified operators only), electronic
Load resistance	IK08

Source info

Integrated source	Integrated LED module
Repleaceable source	NO
Power	LED 10W
Emission	Direct
Max consuption	max 10 W
Features LED	LED SMD
CCT	4000 K
Duration LED (t. 25°c)	20000 h
CRI	> 80
SDCM	3
Light beam	105°
Light beam flux	1250 lm
Useful light flux	1030 lm
Standby power	< 0.50

IDEAL LUX s.r.l.
Via Taglio Destro, 32, 30035 Mirano (Venezia)
Tel +39 041 5790500 | **Fax** +39 041 8872349 | **E-mail** info@ideal-lux.com
www.ideal-lux.com