Pobrano z mamadecor.pl

Steel

rev. 27-04-2022

General info

Technical - Linear system

Indoor ceiling mounted linear fitting with multiple integrated LED sources and direct/indirect light emission

Ean	8021696267142
Item	STEEL ACCENT BK 3000K
Installation	Ceiling
Guarantee	5 years
Gross weight	2.47 kg
Volume	0.017817 m^3

Technical info

Net weight	1.98 kg
Insulation class	I
Protection index	IP20
Operating temperature	0° ~ +40 °C
Dimmer	Non-dimmable, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included
	YES (by qualified operators only), electronic, osram

Source info

Integrated source	Integrated LED module
Repleaceable source	YES (by qualified operators only)
Power	36W
Emission	Direct + Indirect
Max consuption	max 36 W
Features LED	LED SMD SAMSUNG
CCT	3000 K
Duration LED (t. 25°c)	50000 h
CRI	> 90
SDCM	3
Light beam	60+110°
UGR Maximum	< 16
Light beam flux	3000 lm
Useful light flux	3620 lm
Standby power	< 0.50

IDEAL LUX s.r.l.
Via Taglio Destro, 32, 30035 Mirano (Venezia)
Tel +39 041 5790500 | **Fax** +39 041 8872349 | **E-mail** info@ideal-lux.com
www.ideal-lux.com