Pobrano z mamadecor.pl

One

rev. 24-08-2022

General info

Technical - Recessed

Indoor wall or ceiling recessed projector with integrated LED sources and direct light emission

Ean	8021696274775
Item	ONE 2W D2,5
Installation	Recessed (Ceiling, Wall)
Guarantee	5 years
Gross weight	0.09 kg
Volume	6e-05 m^3

Technical info

Net weight	0.07 kg
Insulation class	II
Protection index	IP20
Operating temperature	0° ~ +40 °C
Dimmer	Non-dimmable, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	Separate, included
	YES (by qualified operators only), electronic
Recessed specifications	Ø 25 - h. 30 , 2-10

Source info

Integrated source	Integrated LED module
Repleaceable source	YES (by qualified operators only)
Power	LED 2W
Emission	Direct
Max consuption	max 2 W
Features LED	LED SMD
CCT	3000 K
Duration LED (t. 25°c)	30000 h
CRI	> 90
SDCM	5
Light beam	30°
Light beam flux	130 lm
Useful light flux	70 lm
Photobiological risk	2
Standby power	< 0.50

IDEAL LUX s.r.l.
Via Taglio Destro, 32, 30035 Mirano (Venezia)
Tel +39 041 5790500 | **Fax** +39 041 8872349 | **E-mail** info@ideal-lux.com
www.ideal-lux.com