Pobrano z mamadecor.pl

# Display

rev. 24-08-2022

## General info

### Technical - Spotlights and Tracks

Indoor track mounted linear fitting with integrated LED sources and direct light emission

| | |
|---|---|
| **Ean** | 8021696283661 |
| **Item** | DISPLAY UGR D1595 4000K WH |
| **Installation** | Eutrac 3-phase track (Ceiling) |
| **Guarantee** | 5 years |
| **Gross weight** | 1.98 kg |
| **Volume** | 0.01734 $m^3$ |

## Technical info

| | |
|---|---|
| **Net weight** | 1.57 kg |
| **Insulation class** | II |
| **Protection index** | IP20 |
| **Operating temperature** | 0° ~ +40 °C |
| **Dimmer** | Non-dimmable, On-Off |
| **Power output** | 220-240 V AC 50/60 Hz |
| **Power supply** | In-built, included |
| | NO, electronic |
| **Accessories not included** | Link on-off profile |

## Source info

| | |
|---|---|
| **Integrated source** | Integrated LED module |
| **Repleaceable source** | YES (by qualified operators only) |
| **Power** | 40W |
| **Emission** | Direct |
| **Max consuption** | max 40,00 W |
| **Features LED** | LED SMD SAMSUNG |
| **CCT** | 4000 K |
| **Duration LED (t. 25°c)** | 50000 h |
| **CRI** | > 80 |
| **SDCM** | 3 |
| **Light beam** | 70° |
| **UGR Maximum** | < 22 |
| **Light beam flux** | 6450 lm |
| **Useful light flux** | 3600 lm |
| **Photobiological risk** | 1 |
| **Standby power** | < 0.50 |

**IDEAL LUX s.r.l.**
Via Taglio Destro, 32, 30035 Mirano (Venezia)
**Tel** +39 041 5790500 | **Fax** +39 041 8872349 | **E-mail** info@ideal-lux.com
www.ideal-lux.com