Pobrano z mamadecor.pl

Display

rev. 24-08-2022

General info

Technical - Spotlights and Tracks

Indoor track mounted linear fitting with integrated LED sources and diffuse light emission

Ean	8021696283722
Item	DISPLAY WIDE D1125 3000K WH
Installation	Eutrac 3-phase track (Ceiling)
Guarantee	5 years
Gross weight	1.12 kg
Volume	0.012444 m^3

Technical info

Net weight	0.77 kg
Insulation class	II
Protection index	IP20
Operating temperature	0° ~ +40 °C
Dimmer	Non-dimmable, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included
	NO, electronic
Accessories not included	Link on-off profile

Source info

Integrated source	Integrated LED module
Repleaceable source	YES (by qualified operators only)
Power	40W
Emission	Diffuse
Max consuption	max 40,00 W
Features LED	LED SMD SAMSUNG
CCT	3000 K
Duration LED (t. 25°c)	50000 h
CRI	> 80
SDCM	3
Light beam	125°
Light beam flux	5750 lm
Useful light flux	3250 lm
Photobiological risk	1
Standby power	< 0.50

IDEAL LUX s.r.l.
Via Taglio Destro, 32, 30035 Mirano (Venezia)
Tel +39 041 5790500 | **Fax** +39 041 8872349 | **E-mail** info@ideal-lux.com
www.ideal-lux.com