Pobrano z mamadecor.pl

Diesis

rev. 24-08-2022

General info

DECORATIVO - Floor

Indoor floor adjustable lamp with integrated LED sources, in-built switch and direct light emission

Ean	8021696285344
Item	DIESIS PT OTTONE
Installation	Floor
Guarantee	5 years
Gross weight	4.26 kg
Volume	0.022165 m^3

Technical info

Net weight	3.5 kg
Insulation class	II
Protection index	IP20
Operating temperature	0° ~ +40 °C
Dimmer	Non-dimmable, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included
	YES, electronic
Adjustability	vert. 0°-90° , orizz. 0°-350°

Source info

Integrated source	Integrated LED module
Repleaceable source	YES (by qualified operators only)
Power	LED 4,5W
Emission	Direct
Max consuption	max 4,50 W
Features LED	LED COB
CCT	3000 K
Duration LED (t. 25°c)	20000 h
CRI	> 80
SDCM	3
Light beam flux	300 lm
Useful light flux	280 lm
Photobiological risk	1
Standby power	< 0.50

IDEAL LUX s.r.l.
Via Taglio Destro, 32, 30035 Mirano (Venezia)
Tel +39 041 5790500 | **Fax** +39 041 8872349 | **E-mail** info@ideal-lux.com
www.ideal-lux.com