Pobrano z mamadecor.pl

Omega round

rev. 24-08-2022

General info

Outdoor - Wall

Outdoor ceiling or wall mounted adjustable projector with integrated LED sources and direct light emission

Ean	8021696285504
Item	OMEGA AP ROUND NERO 4000K
Installation	Ceiling, Wall
Guarantee	5 years
Gross weight	0.55 kg
Volume	0.0012 m^3

Technical info

Net weight	0.5 kg
Insulation class	I
Protection index	IP54
Operating temperature	-15° ~ +45 °C
Dimmer	Non-dimmable, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included
Adjustability	YES (by qualified operators only), electronic vert. 0°-90°

Source info

Integrated source	Integrated LED module
Repleaceable source	NO
Power	LED 7W
Emission	Direct
Max consuption	max 7 W
Features LED	LED COB
CCT	4000 K
Duration LED (t. 25°c)	25000 h
CRI	> 80
Light beam	120°
Light beam flux	650 lm
Useful light flux	550 lm
Standby power	< 0.50

IDEAL LUX s.r.l.
Via Taglio Destro, 32, 30035 Mirano (Venezia)
Tel +39 041 5790500 | **Fax** +39 041 8872349 | **E-mail** info@ideal-lux.com
www.ideal-lux.com