Pobrano z mamadecor.pl

Zig zag

rev. 24-08-2022

General info

DECORATIVO - Wall

Indoor wall mounted linear fitting with multiple integrated LED sources and indirect light emission

Ean	8021696287072
Item	ZIG ZAG AP D75 3000K OTTONE
Installation	Wall
Guarantee	5 years
Gross weight	1.3 kg
Volume	0.00525 m^3

Technical info

Net weight	1.04 kg
Insulation class	I
Protection index	IP20
Operating temperature	0° ~ +40 °C
Dimmer	Non-dimmable, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included
	YES (by qualified operators only), electronic

Source info

Integrated source	Integrated LED module
Repleaceable source	NO
Power	LED 30W
Emission	Indirect
Max consuption	max 30 W
Features LED	LED SMD SAMSUNG
CCT	3000 K
Duration LED (t. 25°c)	50000 h
CRI	> 80
Light beam flux	4100 lm
Useful light flux	3680 lm
Standby power	< 0.50

IDEAL LUX s.r.l.
Via Taglio Destro, 32, 30035 Mirano (Venezia)
Tel +39 041 5790500 | **Fax** +39 041 8872349 | **E-mail** info@ideal-lux.com
www.ideal-lux.com