Pobrano z mamadecor.pl

Diesis

rev. 21-03-2023

General info

Indoor - Table lamps

Ean	8021696291109
Item	DIESIS TL OTTONE
Installation	Table lamps
Guarantee	5 years
Gross weight	3.1 kg
Volume	0.063687 m^3

Technical info

Net weight	1.7 kg
Insulation class	II
Protection index	IP20
Compliance	CE
Operating temperature	0° ~ +40 °C
Dimmer	Dimmable, Dimmer on board
Power output	220-240 V AC 50/60 Hz Integrated switch button Touch switch
Power supply	Separate, included Replaceable, electronic
Adjustability	vert. 0°-90° , orizz. 0°-350°

Source info

Integrated source	Integrated LED module
Repleaceable source	No
Power	LED 6,5 W
Emission	Direct
Max consuption	max 6,50 W
Features LED	LED COB BRIDGELUX
CCT	3000 K
Duration LED (t. 25°c)	20000 h
CRI	> 90
Light beam	20°
Light beam flux	600 lm
Useful light flux	500 lm
Standby power	< 0.50 W

IDEAL LUX s.r.l.
Via Taglio Destro, 32, 30035 Mirano (Venezia)
Tel +39 041 5790500 | **Fax** +39 041 8872349 | **E-mail** info@ideal-lux.com
www.ideal-lux.com