Pobrano z mamadecor.pl

Komodo

rev. 21-03-2023

General info

Indoor - Wall lamps

Ean	8021696291789
Item	KOMODO-1 AP BIANCO
Installation	Wall lamps
Guarantee	5 years
Gross weight	0.82 kg
Volume	0.006006 m^3

Technical info

Net weight	0.7 kg
Insulation class	II
Protection index	IP20
Compliance	CE
Operating temperature	0° ~ +40 °C
Dimmer	Non-dimmable, On-Off
Power output	220-240 V AC 50/60 Hz Integrated switch button Integrated USB socket
Power supply	In-built, included Replaceable (by qualified operators only), electronic
Adjustability	vert. 0-90°, orizz. 0-180°

Source info

Integrated source	Integrated LED module
Repleaceable source	Replaceable (by qualified operators only)
Power	LED 4,5 W
Emission	Direct
Max consuption	max 4,50 W
Features LED	LED SMD
CCT	3000 K
Duration LED (t. 25°c)	20000 h
CRI	> 80
Light beam	25°
Light beam flux	250 lm
Useful light flux	210 lm
Photobiological risk	2
Standby power	< 0.50 W

IDEAL LUX s.r.l.
Via Taglio Destro, 32, 30035 Mirano (Venezia)
Tel +39 041 5790500 | **Fax** +39 041 8872349 | **E-mail** info@ideal-lux.com
www.ideal-lux.com