Pobrano z mamadecor.pl

# Fox

rev. 21-03-2023

## General info

### Technical - Spotlights and Tracks

| | |
|---|---|
| **Ean** | 8021696302607 |
| **Item** | FOX 25W CRI90 3000K 1-10V WH |
| **Installation** | Spotlights and Tracks |
| **Guarantee** | 5 years |
| **Gross weight** | 0.81 kg |
| **Volume** | 0.004995 $m^3$ |

## Technical info

| | |
|---|---|
| **Net weight** | 0.71 kg |
| **Insulation class** | II |
| **Protection index** | IP20 |
| **Compliance** | CE |
| **Operating temperature** | 0° ~ +40 °C |
| **Dimmer** | Dimmable, 1-10V |
| **Power output** | 220-240 V AC 50/60 Hz |
| **Power supply** | In-built, included<br>NO, electronic |
| **Accessories not included** | Single connection 1-10V/DALI, Link 1-10V/DALI profile |

## Source info

| | |
|---|---|
| **Integrated source** | Integrated LED module |
| **Repleaceable source** | Replaceable (by qualified operators only) |
| **Power** | 25 W |
| **Emission** | Direct |
| **Max consuption** | max 25,00 W |
| **Features LED** | LED COB BRIDGELUX |
| **CCT** | 3000 K |
| **Duration LED (t. 25°c)** | 30000 h |
| **CRI** | > 90 |
| **SDCM** | 3 |
| **Light beam** | 35° |
| **Light beam flux** | 2450 lm |
| **Useful light flux** | 2010 lm |
| **Photobiological risk** | 1 |
| **Standby power** | < 0.50 W |

**IDEAL LUX s.r.l.**
Via Taglio Destro, 32, 30035 Mirano (Venezia)
**Tel** +39 041 5790500 | **Fax** +39 041 8872349 | **E-mail** info@ideal-lux.com
www.ideal-lux.com