Pobrano z mamadecor.pl

Fox

rev. 21-03-2023

General info

Technical - Spotlights and Tracks

Ean	8021696302614
Item	FOX 25W CRI90 3000K DALI BK
Installation	Spotlights and Tracks
Guarantee	5 years
Gross weight	0.81 kg
Volume	0.004995 m^3

Technical info

Net weight	0.71 kg
Insulation class	II
Protection index	IP20
Compliance	CE
Operating temperature	0° ~ +40 °C
Dimmer	Dimmable, DALI
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included NO, electronic
Accessories not included	Single connection 1-10V/DALI, Link 1-10V/DALI profile

Source info

Integrated source	Integrated LED module
Repleaceable source	Replaceable (by qualified operators only)
Power	25 W
Emission	Direct
Max consuption	max 25,00 W
Features LED	LED COB BRIDGELUX
CCT	3000 K
Duration LED (t. 25°c)	30000 h
CRI	> 90
SDCM	3
Light beam	35°
Light beam flux	2450 lm
Useful light flux	2010 lm
Photobiological risk	1
Standby power	< 0.50 W

IDEAL LUX s.r.l.
Via Taglio Destro, 32, 30035 Mirano (Venezia)
Tel +39 041 5790500 | **Fax** +39 041 8872349 | **E-mail** info@ideal-lux.com
www.ideal-lux.com