Pobrano z mamadecor.pl

STAVANGER 1246

Stavanger 1246XX0011
23.07.2021 v.11.3
www.norlys.com

Type of luminaire

Type of lumianire	Bollard.
Photometric body	Indirect light with rotationally symmetrical light distribution facing down.
Characteristics of the luminaire	Bollard luminaire of stable and durable construction. For lighting private areas and public spaces

General information

Materials	Powder painted aluminum cast. Lens - satin PMMA plastic. Silicone gasket. Nylon6 cable gland.
Mounting method	Mounting of the luminaire: 3 holes ø9mm with a diameter of ø145mm every 120°
Terminal	Connection terminals: max 5x4mm², Possibility to connect the luminaire in loops max 5x2,5mm². Round insulated cable with a diameter of ø8 ... 17mm. The luminaire is equipped with holes for mounting the TH-35 mounting rail, 10cm long
Type of light source	E27 lamp
Net weight of luminaire	6,44kg
Box dimensions [cm]	22,5x22,5x58,5

Technical data

E27 lamp	QA55 / LED A55..60
Light source wattage	max 46W / LED 9W

This product contains light source of energy efficiency class

Possibility to order the luminaire with LED E27 Philips Master LED bulb 806lm/8,5W/2700K (dimmable)

Accessories sold separately

1230	Concreting anchor
1231	Ground anchor
1232	Anchoring support
46999021	LED E27 lamp

Recommended light sources

Osram LED Parathom Classic E27	Philips Master LEDbulb / Ledbulb Classic E27
Osram ECO PRO Classic 46<=>60W E27	Philips ECO Classic 42<=>60W E27

Files to download

Manual

Indexes

Index	Color	RAL
1246AL	ALUMINIUM	9006
1246GR	GRAPHITE	7016

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Please read the manual before installing. Due to the dynamic development of lighting technology, additional information is available upon request. LED module must be replaced by a qualified person following applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not impair the quality of the luminaire.