

ARENDAL 1250

Pobrano z mamadecor.pl

Arendal 1250XX0009
23.07.2021 v.09.3
www.norlys.com





Type of luminaire

Type of lumianire	Wall luminaire.
Photometric body	Uncovered light.
Characteristics of the luminaire	Modern design luminaire with a combination of decorative crystal lampshade and metal lamp enclosure.

General information

Materials	Powder painted aluminum cast. Lens - crystal glass, satin inside. Lens may change to light amber colour over time. Nylon6 cable gland.
Mounting method	Fixing of the luminaire: 2 holes ø5mm , spacing 34x54mm.
Terminal	Connection terminals: max 2x2,5mm², possibility to connect luminaire in loop max 2x1,5mm². A round wire in the isolation with a diameter of max ø12,5mm.
Type of light source	E14 lamp
Net weight of luminaire	2,3kg
Box dimensions [cm]	27x11x20,5

Technical data

E14 lamp	QB35 / LED B35
Light source wattage	max 46W / LED 6W

This product contains light source of energy efficiency class

Recommended light sources

Osram LED Parathom Retrofit/Advanced/ Classic B38 E14	Philips Master LED luster/candle/frosted B38 E14
Osram ECO PRO Classic 46<=>60W QB35 E14	Philips ECO Classic 42<=>60W QB35 E14

Files to download

Manual

Indexes

Index	Color	RAL
1250B	BLACK	9005
1250GR	GRAPHITE	7016

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Please read the manual before installing. Due to the dynamic development of lighting technology, additional information is available upon request. LED module must be replaced by a qualified person in accordance with applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not impair the quality of the luminaire.