EGERSUND 1280

Pobrano z mamadecor.pl

Egersund 1280XX0013
23.07.2021 v.13.18
www.norlys.com

Type of luminaire

Type of lumianire	Bollard.
Photometric body	Light with rotationally symmetrical light distribution.
Characteristics of the luminaire	Modern design luminaire. For lighting gardens, private and public areas

General information

Materials	Powder painted aluminum cast. Lens - transparent plastic PMMA. Silicone gasket. Nylon6 cable gland.
Mounting method	Mounting of the luminaire: 3 holes ø9mm on a diameter ø65mm, every120°
Terminal	Connection terminals: max 5x4mm², Possibility to connect luminaire in loop max 5x4mm², Round insulated cable with a diameter ø8...17mm
Type of light source	LED module, power supply
Light control	Non-dimmable luminaire
Net / gross weight of luminaire	11,63kg / 13,46kg
Box dimensions [cm]	23x22x113

Technical data

5 LED modules	Cree JK3030 no.1805004 (Datasheet)
Driver	Philips Xitanium 20W/m 0.15-0,5A 54V 230V (Datasheet)
Light source wattage	17,9W
Luminaire wattage	22W
Lamp luminous flux	2434lm
Luminaire luminous flux	1586lm
Light source efficiency	136lm/W
Efficiency of the luminaire	72,1lm/W
ULOR	10%
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	>50 000h
LED photobiological threat	RG0 or RG1
Power Factor luminaire	PF>0,98
Ta Rated temperature	+25°C

This product contains light sources of energy efficiency class

Inrush current	18A/250µs

Maximum number of luminaires of this type per MCB:

B 10A: 21, **B 16A**: 34, **C 10A**: 35, **C 16A**: 57

Accessories sold separately

1230ZX0009	Concreting anchor
1231GA0009	Ground anchor
1232GA0010	Anchoring support

Spare parts

0912800004	Power supply.
09128010	Lens.
46999560	LED module.

Files to download

Photometric LDT files	Photometric IES files
Manual	BIM Revit
BIM ArchiCAD	

Indexes

Index	Color	RAL
1280AL	ALUMINIUM	9006
1280GR	GRAPHITE	7016

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Please read the manual before installing. Due to the dynamic development of lighting technology, additional information is available upon request. LED module must be replaced by a qualified person in accordance with applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not impair the quality of the luminaire.