EGERSUND MINI 1291

Pobrano z mamadecor.pl

Egersund mini
1291XX0012
23.07.2021 v.12.5
www.norlys.com

Type of luminaire

Type of lumianire	Bollard.
Photometric body	Light with rotationally symmetrical light distribution.
Characteristics of the luminaire	Modern design luminaire. For lighting gardens and other private and public areas.

General information

Materials	Powder painted aluminum cast. Lens - transparent plastic PMMA. Silicone gasket. Nylon6 cable gland.
Mounting method	Fixing of the luminaire: 3 holes of ø9mm on a diameter ø65mm every 120 °.
Terminal	Connection terminals: max 3x4mm², possibility to connect luminaire in loop max 5x4mm². A round wire in the isolation with a diameter ø8...17mm.
Type of light source	LED module AC integrated
Light control	Phase-dimming (TRIAC).
Net / gross weight of luminaire	3,43kg / 4,08kg
Box dimensions [cm]	15,5x15,5x55

Technical data

LED module	Lumens DLM 90C 10W xxx 230V /A V0.1 (Datasheet)
External control	Dimmers Lumens LED AC (User manual)
Light source wattage	10W
Luminaire wattage	10W
Lamp luminous flux	1100lm
Luminaire luminous flux	826lm
Light source efficiency	110lm/W
Efficiency of the luminaire	82,6lm/W
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	50 000h
Power Factor luminaire	PF >0,90
Ta Rated temperature	+25°C
This product contains light source of energy efficiency class	
Inrush current	150mA / 500µs

Accessories sold separately

205ZX0010	Concreting anchor.
206GA0010	Ground anchor.
206GA0S10	Anchoring support.

Spare parts

0912900201	Electric set.

Files to download

Photometric LDT files	Photometric IES files
Manual	BIM Revit
BIM ArchiCAD	

Indexes

Index	Color	RAL
1291AL	ALUMINIUM	9006
1291GR	GRAPHITE	7016

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Please read the manual before installing. Due to the dynamic development of lighting technology, additional information is available upon request. LED module must be replaced by a qualified person in accordance with applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not impair the quality of the luminaire.