HITRA 1330

Pobrano z mamadecor.pl

Hitra 1330XX0009
23.07.2021 v.09.3
www.norlys.com

Type of luminaire

Type of lumianire	Wall luminaire.
Photometric body	Covered light facing down.
Characteristics of the luminaire	Modern design luminaire. For lighting private areas and public spaces.

General information

Materials	Powder painted aluminum cast. Lens - safety glass, transparent. Silicone gasket. EPDM cable gland.
Mounting method	Fixing of the luminaire: 2 holes ø4mm, spacing 104mm.
Terminal	Connection terminals: max 3x2,5mm², possibility to connect luminaire in loop max 3x1,5mm². A round wire in the isolation with a diameter ø7...10,5mm.
Type of light source	LED module AC integrated
Light control	Non-dimmable luminaire
Net / gross weight of luminaire	1,41kg / 1,58kg
Box dimensions [cm]	23x16x8

Technical data

LED module	Philips Fortimo DLM ES 1100/8xx G2 (Datasheet)
Light source wattage	9,5W
Luminaire wattage	9,5W
Lamp luminous flux	1080lm
Luminaire luminous flux	920lm
Light source efficiency	113,7lm/W
Efficiency of the luminaire	96,8lm/W
ULOR	0%
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	50 000h
Power Factor luminaire	PF > 0,9
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class

Inrush current	2,98A / 34,07µs

Maximum number of luminaires of this type per MCB:

B 10A: 144, **B 16A**: 230, **C 10A**: 239, **C 16A**: 391

Spare parts

ZS1330zx0009	Service set.

Files to download

Photometric LDT files	Photometric IES files
Manual	BIM ArchiCAD

Indexes

Index	Color	RAL
1330AL	ALUMINIUM	9006
1330GR	GRAPHITE	7016
1330W	WHITE	9003

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Please read the manual before installing. Due to the dynamic development of lighting technology, additional information is available upon request. LED module must be replaced by a qualified person in accordance with applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not impair the quality of the luminaire.