Pobrano z mamadecor.pl

# NAMSOS MINI 1340

Namsos mini 1340XX0010
23.07.2021 v.10.13
www.norlys.com

## Type of luminaire

| | |
|---|---|
| Type of lumianire | Recessed wall luminaire. |
| Photometric body | Covered light facing down. |
| Characteristics of the luminaire | Luminaire designed to illuminate stairs, steps, staircases, communication lines, ceiling illumination and many other architectural applications. |

## General information

| | |
|---|---|
| Materials | Powder painted aluminum cast. Lens - safety glass, satin. Silicone gasket. EPDM cable gland. |
| Mounting method | Fixing of the luminaire: wall-mounted - hole 105x105x110, fixing in the layered wall - hole 82x82x82.<br>Includes template for easy installation of the luminaire. |
| Terminal | Connection terminals: max 3x2,5mm², possibility to connect luminaire in max 3x1,5mm². A round wire in the isolation with a diameter of ø7...10,5mm. |
| Type of light source | LED module AC integrated |
| Light control | Phase-dimming (TRIAC). |
| Net / gross weight of luminaire | 0,55kg / 0,65kg |
| Box dimensions [cm] | 12x12x13 |

## Technical data

| | |
|---|---|
| LED module | Lumens EDC 38C 4W xxx 230V A Ver.1.2 (Datasheet) |
| External control | Dimmers Lumens LED AC (User manual) |
| Light source wattage | 4W |
| Luminaire wattage | 4W |
| Lamp luminous flux | 439lm |
| Luminaire luminous flux | 59lm |
| Light source efficiency | 109,8lm/W |
| Efficiency of the luminaire | 14,8lm/W |
| Color temperature | 3000K |
| Colour consistency (McAdam ellipse) | SDCM3 |
| Colour rendering index CRI | 80 |
| Rated life time L70/B50 at 25°C | >50 000h |
| LED photobiological threat | RG0 or RG1 |
| Power Factor luminaire | PF >0,98 |
| THD factor | < 20% |
| Ta Rated temperature | +25°C |
| Max ambient temperature | -35...+35°C |
| This product contains light source of energy efficiency class | |
| Inrush current | 17mA / 60ms |

## Spare parts

| | |
|---|---|
| 46999566 | LED module. |

## Files to download

| | |
|---|---|
| Photometric LDT files | Photometric IES files |
| Manual | BIM Revit |
| BIM ArchiCAD | |

## Indexes

| Index | Color | RAL |
|---|---|---|
| **1340AL** | ALUMINIUM | 9006 |
| **1340GR** | GRAPHITE | 7016 |

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Please read the manual before installing. Due to the dynamic development of lighting technology, additional information is available upon request. LED module must be replaced by a qualified person in accordance with applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not impair the quality of the luminaire.