ASKER POLE 1360

Pobrano z mamadecor.pl

Asker pole 1360XX0010
24.01.2020 v.10.1
www.norlys.com

Type of luminaire

Type of lumianire	Pole luminaire (light construction).
Photometric body	Single-sided, symmetric light facing down.
Characteristics of the luminaire	Pole luminaire with 2160mm high (two-part luminaire). For lighting private areas, public spaces and other architectural concepts.

General information

Materials	Extruded aluminum profile, powder coated. Lens - transparent polycarbonate with structure, UV stabilized. Silicone gasket.
Mounting method	Fixing of the luminaire: 4 holes on a diameter ø12mm, spacing 200x200mm. Art. 1360: 2-parts pole luminaire. Other accessories need to be purchased separately.
Terminal	Connection terminals: max 3x2,5mm², possibility to connect luminaire in loop max 3x2,5mm². A round wire in the isolation with a diameter of max ø12,5mm.
Type of light source	LED module AC integrated
Light control	Phase-dimming (TRIAC).
Net / gross weight of luminaire	10,54kg / 12,11kg
Box dimensions [cm]	25x115x56
Side area of luminaire	0,23m²

Technical data

2 LED modules	Lumens LNM/280X30/9W/830/230V
Light source wattage	18W
Luminaire wattage	18W
Lamp luminous flux	1710lm
Luminaire luminous flux	962lm
Light source efficiency	95lm/W
Efficiency of the luminaire	53,4lm/W
ULOR	0%
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	50 000h
Energy Efficiency Index	
Power Factor luminaire	PF > 0,99
Ta Rated temperature	+25°C
Inrush current	108,8mA/500µs

Maximum number of luminaires of this type per MCB:

B 10A: 19, **B 16A**: 31, **C 10A**: 32, **C 16A**: 53

Accessories sold separately

116ZX0009	Concreting anchor (anchor L190mm).
117GA0009	Ground anchor.
118GA0009	Anchoring support.
119ZX0009	Concreting anchor (anchor L700mm).

Spare parts

06136000	Lens.
08136000	Gasket.
46999388	LED module AC integrated.

Files to download

Photometric LDT files	Photometric IES files
Manual	

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Please read the manual before installing. Due to the dynamic development of lighting technology, additional information is available upon request. LED module must be replaced by a qualified person in accordance with applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not impair the quality of the luminaire.

ASKER POLE 1360

Pobrano z mamadecor.pl

Indexes

Index	Color	RAL
1360AL	ALUMINIUM	9006
1360B	BLACK	9005
1360GR	GRAPHITE	7016

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Please read the manual before installing. Due to the dynamic development of lighting technology, additional information is available upon request. LED module must be replaced by a qualified person in accordance with applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not impair the quality of the luminaire.