MANDAL 1371

Pobrano z mamadecor.pl

Mandal 1371XX0010
23.07.2021 v.10.2
www.norlys.com

Type of luminaire

Type of lumianire	Wall luminaire.
Photometric body	Double-sided light facing up and down.
Characteristics of the luminaire	Wall-mounted luminaire with modern design. For lighting private areas and public spaces.

General information

Materials	Base - galvanized steel. Front - galvanized steel or powder coated galvanized steel. Lens - safety glass, transparent. Silicone gasket.
Mounting method	Fixing of the luminaire: 2 holes ø4,2mm, spacing 45mm.
Terminal	Zaciski podłączeniowe: max 3x2,5mm², możliwość podłączenia oprawy w pętle max 3x1,5mm². Przewód w oponie okrągłej o średnicy ø7...10,5mm.
Type of light source	LED Gu10 lamp
Net / gross weight of luminaire	0,94kg / 1,35kg
Box dimensions [cm]	20x13x10

Technical data

2 LED GU10 lamps.	LED PAR16
Light source wattage	2 x max 4W
Lamp luminous flux	2 X ~ 265lm
Ta Rated temperature	+25°C

This product contains light sources of energy efficiency class

Possibility to order luminaire with LED GU10 lamp type Philips Master LED ExpertColor 256lm/3,9W/2700K/25D (dimmable).

Accessories sold separately

46102507	

Recommended light sources

Osram LED Parathom Advanced / Pro max 4W PAR16 Gu10	Philips Master LED max 4W PAR16 Gu10

Files to download

Photometric LDT files	Photometric IES files
Manual	BIM ArchiCAD

Indexes

Index	Color	RAL
1371B	BLACK	9005
1371BC	BLACK/COPPER	-
1371GA	GALVANIZED	-

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Please read the manual before installing. Due to the dynamic development of lighting technology, additional information is available upon request. LED module must be replaced by a qualified person in accordance with applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not impair the quality of the luminaire.