MANDAL 1373

Pobrano z mamadecor.pl

Mandal 1373XX0010
23.07.2021 v.10.2
www.norlys.com

Type of luminaire

Type of lumianire	Wall luminaire.
Photometric body	Single-sided, symmetric light facing down.
Characteristics of the luminaire	Wall-mounted luminaire with modern design. For lighting private areas and public spaces.

General information

Materials	Base - galvanized steel. Front - galvanized steel or powder coated galvanized steel. Lens - safety glass, transparent. Silicone gasket.
Mounting method	Fixing of the luminaire: 2 holes ø4,2mm, spacing 45mm.
Terminal	Connection terminals: max 3x2,5mm², possibility to connect luminaire in loop max 3x1,5mm². A round wire in the isolation with a diameter of ø7...10,5mm.
Type of light source	LED Gu10 lamp, 25D
Light control	Phase-dimming (TRIAC).
Net / gross weight of luminaire	0,89kg / 0,97kg
Box dimensions [cm]	12,5x13x10

Technical data

LED GU10 lamp	Philips Master LED ExpertColor 25D 3,9W<=> 35W Gu10
Light source wattage	3,9W
Luminaire wattage	3,9W
Lamp luminous flux	265lm
Luminaire luminous flux	250lm
Light source efficiency	67,9lm/W
Efficiency of the luminaire	64,1lm/W
Color temperature	2700K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	97
Rated life time L70/B50 at 25°C	40 000h
Power Factor luminaire	PF 0,8
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class

Recommended light sources

Osram LED Parathom Advanced / Pro max 4W PAR16 Gu10	Philips Master LED max 4W PAR16 Gu10

Spare parts

46102507	LED Gu10 lamp.

Files to download

Photometric LDT files	Photometric IES files
Manual	BIM ArchiCAD

Indexes

Index	Color	RAL
1373B	BLACK	9005
1373GA	GALVANIZED	-

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Please read the manual before installing. Due to the dynamic development of lighting technology, additional information is available upon request. LED module must be replaced by a qualified person in accordance with applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not impair the quality of the luminaire.