LILLESAND 1380

Pobrano z mamadecor.pl

Lillesand 1380XX0010
23.07.2021 v.10.2
www.norlys.com

Type of luminaire

Type of lumianire	Bollard.
Photometric body	Light with rotationally symmetrical light distribution.
Characteristics of the luminaire	Modern design luminaire. For lighting gardens, private areas and public spaces.

General information

Materials	Powder painted aluminum cast. Lens - satin PMMA plastic. Silicone gasket. Nylon6 cable gland.
Mounting method	Fixing of the luminaire: 3 holes ø9mm on a diameter ø65mm every 120°.
Terminal	Connection terminals: max 2x2,5mm², possibility to connect in loop max 2x2,5mm². A round wire in the isolation with a diameter of ø8...12,5mm.
Type of light source	E27 lamp
Net / gross weight of luminaire	4,75kg / 5,73kg
Box dimensions [cm]	16x16x93

Technical data

E27 lamp	QA55 / LED A55..60
Light source wattage	MAX 46W / LED 9W
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class

Possibility to order the luminaire with LED E27 Philips Master LEDbulb 806lm / 8,5W / 2700K (dimmable).
The attached photometric test results apply to the luminaire, where the above-mentioned E27 LED lamp was mounted.

Accessories sold separately

205ZX0010	Concreting anchor.
206GA0010	Ground anchor.
206GA0S10	Anchoring support.
46999021	LED E27 lamp.

Recommended light sources

Osram ECO PRO Classic 46<=>60W E27	Philips ECO Classic 42<=>60W E27
Osram LED Parathom Classic / Retrofit E27	Philips Master LEDbulb / Classic / CorePro E27

Files to download

Photometric LDT files	Photometric IES files
Manual	

Indexes

Index	Color	RAL
1380AL	ALUMINIUM	9006
1380GR	GRAPHITE	7016

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Please read the manual before installing. Due to the dynamic development of lighting technology, additional information is available upon request. LED module must be replaced by a qualified person in accordance with applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not impair the quality of the luminaire.