SKI 1392

Pobrano z mamadecor.pl

SKI 1392XX0010
23.07.2021 v.10.5
www.norlys.com

Type of luminaire

Type of lumianire	Wall luminaire.
Photometric body	Single-sided light facing down.
Characteristics of the luminaire	A luminaire with a wide range of applications, used for general and decorative lighting of wall surfaces, facades, and other architectural concepts

General information

Materials	Base - galvanized steel. Front - galvanized steel or powder coated galvanized steel. Lens - transparent polycarbonate with structure, UV stabilized. Silicone gasket.
Mounting method	Mounting of the luminaire: 2 holes ø4.2mm, spacing 122mm
Terminal	Connection terminals: max 3x2.5mm², Possibility to connect the luminaire in loops, max 3x1.5mm². Round insulated cable with a diameter of ø7 ... 10.5mm
Type of light source	LED module, power supply
Light control	Trailing edge dimming
Net / gross weight of luminaire	0,94kg / 0,99kg
Box dimensions [cm]	22,5x15,5x15

Technical data

LED module	Philips Strip OC 0.5ft 550lm 8xx FC HV5 (Datasheet)
Driver	Philips Xitanium 7W 0,35A 20V TE SC 230V (Datasheet)
Light source wattage	4W
Luminaire wattage	5,3W
Lamp luminous flux	653lm
Luminaire luminous flux	346lm
Light source efficiency	163,3lm/W
Efficiency of the luminaire	65,3lm/W
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	>70 000h
Power Factor luminaire	PF 0,96
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class

Inrush current	1A/15,2µs

Maximum number of luminaires of this type per MCB:

B 10A: 157, **B 16A**: 250, **C 10A**: 260, **C 16A**: 425

Spare parts

ZS1392zx0010	Service set.

Files to download

Photometric LDT files	Photometric IES files
Manual	BIM Revit
BIM ArchiCAD	

Indexes

Index	Color	RAL
1392B	BLACK	9005
1392GA	GALVANIZED	-

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no



Before the installation, read the instructions attached to the luminaire. Due to the dynamic development of lighting technology, we provide additional information at the client's request. LED module replaceable by a person with appropriate qualifications, following applicable regulations. Condensation, which may occur in luminaires, is a natural phenomenon and does not affect the quality of the luminaire