HALMSTAD 1400

Pobrano z mamadecor.pl

Halmstad 1400XX0010
23.07.2021 v.10.2
www.norlys.com

Type of luminaire

Type of lumianire	Bollard.
Photometric body	Uncovered light, partly covered from the top.
Characteristics of the luminaire	Bollard luminaire of stable and durable construction. For lighting private areas and public spaces.

General information

Materials	Wood - scandinavian painted pine and hot-dip galvanized steel. Wood - scandinavian painted pine, hot-dip galvanized and powder painted steel. Lens - plastic PMMA in milky color. Silicone gasket.
Mounting method	Fixing of the luminaire: 3 holes ø9mm with a diameter of ø65mm every 120 °.
Terminal	Connection terminals: max 3x2,5mm², possibility to connect luminaire in loop max 3x1,5mm². A round wire in the isolation with a diameter of max ø12,5mm.
Type of light source	E27 lamp
Net / gross weight of luminaire	6,09kg / 6,79kg

Technical data

E27 lamp	QA55 / LED A55..60
Light source wattage	max 46W / LED 9W

This product contains light source of energy efficiency class

Possibility to order the luminaire with LED E27 Philips Master LEDbulb 806lm / 8,5W / 2700K (dimmable).

Accessories sold separately

205ZX0010	Concreting anchor.
206GA0010	Ground anchor.
206GA0S10	Anchoring support.

Recommended light sources

Osram LED Parathom Classic E27	Philips Master LEDbulb / Ledbulb Classic E27
Osram ECO PRO Classic 46<=>60W E27	Philips ECO Classic 42<=>60W E27

Spare parts

06295000	Lens.
08295000	Gasket.

Files to download

Photometric LDT files	Photometric IES files
Manual	BIM ArchiCAD

Indexes

Index	Color	RAL
1400B	BLACK	9005
1400GA	GALVANIZED	-

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Please read the manual before installing. Due to the dynamic development of lighting technology, additional information is available upon request. LED module must be replaced by a qualified person in accordance with applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not impair the quality of the luminaire.