ALTA 1479

Pobrano z mamadecor.pl

Alta 1479XX0012
23.07.2021 v.12.4
www.norlys.com

Type of luminaire

Type of lumianire	Bollard.
Photometric body	Light with rotationally symmetrical light distribution, covered from the top.
Characteristics of the luminaire	A bollard luminaire with a stable and durable structure. For lighting private areas and public areas

General information

Materials	Hot-dip galvanized steel. Hot-dip galvanized and powder-coated steel. Lens - plastic PMMA in milky color. Silicone gasket.
Mounting method	Fixing of the luminaire: 3 holes ø9mm in diameter ø65mm every 120 °. Other accessories must be purchased separately
Terminal	Connection terminals: max 3x2.5mm², possibility to connect the luminaire in loops, max 3x1.5mm². Round insulated cable with a diameter of max ø12.5mm
Type of light source	LED module AC integrated
Light control	Phase-dimming (TRIAC).
Net / gross weight of luminaire	9,3kg / 10,7kg

Technical data

LED module	Lumens EDC 47C 10W xxx 230V A Ver.1.2 (Datasheet)
External control	Dimmers Lumens LED AC (User manual)
Light source wattage	10W
Luminaire wattage	10W
Lamp luminous flux	1098lm
Luminaire luminous flux	159lm
Light source efficiency	109,8lm/W
Efficiency of the luminaire	15,9lm/W
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	>50 000h
LED photobiological threat	RG0 or RG1
Power Factor luminaire	PF > 0,99
THD factor	< 20%
Ta Rated temperature	+25°C
Max ambient temperature	-35...+25°C
This product contains light source of energy efficiency class	
Inrush current	43mA / 60ms

Accessories sold separately

205ZX0010	Concreting anchor
206GA0010	Ground anchor

Spare parts

06291001	Lens.
08288004	Gasket.
ZS1479zx0012	Service set.

Files to download

Photometric LDT files	Photometric IES files
Manual	BIM ArchiCAD

Indexes

Index	Color	RAL
1479B	BLACK	9005
1479GA	GALVANIZED	-

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Before the installation, read the instructions attached to the luminaire. Due to the dynamic development of lighting technology, we provide additional information at the client's request. LED module replaceable by a person with appropriate qualifications, in accordance with applicable regulations.
Condensation, which may occur in luminaires, is a natural phenomenon and does not affect the quality of the luminaire