SUNNFJORD 1508

Pobrano z mamadecor.pl

Sunnfjord 1508XX0010
23.07.2021 v.10.1
www.norlys.com

Type of luminaire

Type of lumianire	Pole luminaire.
Photometric body	An asymmetric distributed and down facing light.
Characteristics of the luminaire	Modern design luminaire, mounted on a telescopic lighting pole with diameter Ø76mm. Tightness of the lighting chamber - IP65.

General information

Materials	Powder painted aluminum cast. Lens - satin polycarbonate, UV stabilized . Silicone gasket.
Mounting method	Fixing of the luminaire: luminaire adjusted to ø76mm lightning pole.
Terminal	4.5 m H05VV-F 3G1 cable, for connection inside the lighting pole (in an appropriately selected electrical installation box).
Type of light source	LED module, power supply
Light control	Non-dimmable luminaire
Net weight of luminaire	8,57kg
Side area of luminaire	0,1m^2

Technical data

LED module	Philips FORTIMO DLM Flex 3000/840 Gen2
Light source wattage	29,3W
Luminaire wattage	31,5W
Lamp luminous flux	4342lm
Color temperature	4000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	>60 000h
Power Factor luminaire	PF 0,98
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class

Inrush current	18A/250µs

Maximum number of luminaires of this type per MCB:

B 10A: 21, **B 16A**: 34, **C 10A**: 35, **C 16A**: 57

Accessories sold separately

1509XX0009	Reduction for Ø60 luminaire to install on Ø76 lighting pole.
3005XX0009	Telescopic lighting pole with adjustable height 3600 ... 4500mm, mounting cap Ø76. Concreting anchor included.
7662ZX0009	Pole connector EK480 IP54, fuse D01 / E14 max. 16A.
7664ZX0009	Concrete foundation for mounting lighting pole.

Spare parts

06150504	Lens.
08150500	Gasket.
46999682	LED module.
46999729	Power supply.

Files to download

Photometric LDT files	Manual

Indexes

Index	Color	RAL
1508AL	ALUMINIUM	9006
1508GR	GRAPHITE	7016

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Please read the manual before installing. Due to the dynamic development of lighting technology, additional information is available upon request. LED module must be replaced by a qualified person in accordance with applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not impair the quality of the luminaire.