ASKER 1510

Pobrano z mamadecor.pl

Asker 1510XX0015
23.07.2021 v.15.8
www.norlys.com

Type of luminaire

Type of lumianire	Wall luminaire.
Photometric body	Double-sided light facing up and down.
Characteristics of the luminaire	Luminaire with a wide range of applications for example for illumination of walls and facade surfaces or any other architectural concepts.

General information

Materials	Powder painted aluminum cast. Lens - transparent polycarbonate with structure, UV stabilized. Silicone gasket. EPDM cable gland.
Mounting method	Fixing of the luminaire: 2 holes ø4,5mm, spacing 180x60mm
Terminal	Connection terminals: max 3x2,5mm², possibility to connect luminaire in loop max 3x1,5mm². A round wire in the isolation with a diameter of ø7...10,5mm.
Type of light source	LED module AC integrated
Light control	Phase-dimming (TRIAC).
Box dimensions [cm]	24x12x9,5

Technical data

LED module	Lumens EDC 57C 8W xxx 230V A FF Ver.1.0 (Datasheet)
Light source wattage	8W
Luminaire wattage	8W
Lamp luminous flux	890lm
Luminaire luminous flux	373lm
Light source efficiency	111,3lm/W
Efficiency of the luminaire	46,6lm/W
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	50 000h
LED photobiological threat	RG0 or RG1
Power Factor luminaire	PF>0,99
THD factor	< 20%
Ta Rated temperature	+25°C
Max ambient temperature	-35...+25°C

This product contains light source of energy efficiency class

Inrush current	2,9mA/34µs

Spare parts

08151000	Gasket.
46999552	LED module.

Files to download

Photometric LDT files	Photometric IES files
Manual	BIM Revit
BIM ArchiCAD	

Indexes

Index	Color	RAL
1510AL	ALUMINIUM	9006
1510B	BLACK	9005
1510GR	GRAPHITE	7016
1510W	WHITE	9003

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Please read the manual before installing. Due to the dynamic development of lighting technology, additional information is available upon request. LED module must be replaced by a qualified person in accordance with applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not impair the quality of the luminaire.