GRIMSTAD 1546

Pobrano z mamadecor.pl

Grimstad 1546XX0010
23.07.2021 v.10.3
www.norlys.com

Type of luminaire

Type of lumianire	Recessed wall luminaire.
Photometric body	Diffused, uncovered light.
Characteristics of the luminaire	The luminaire is suitable for lighting stairs, steps, staircases, pathways, and other places

General information

Materials	Powder painted aluminum cast. Lens - safety glass, milky colour. Silicone gasket. EPDM cable gland.
Mounting method	Mounting of the luminaire: embedded in the wall - hole 258x112x115, fixing in a layered wall - hole 235x96x82
Terminal	Connection terminals: max 3x2.5mm², Possibility to connect the luminaire in loops, max 3x1.5mm². Round insulated cable with a diameter of ø7 ... 10.5mm
Type of light source	E14 lamp
Net / gross weight of luminaire	1,44kg / 1,6kg
Box dimensions [cm]	27x12,5x11,5

Technical data

E14 lamp	QB35
Light source wattage	max 46W / LED 6W

This product contains light source of energy efficiency class

Recommended light sources

Osram LED Parathom Retrofit/Advanced/ Classic B38 E14	Philips Master LED luster/candle/frosted B38 E14
Osram ECO PRO Classic 46<=>60W QB35 E14	Philips ECO Classic 42<=>60W QB35 E14

Spare parts

06152000	Lens.
08154000	Gasket.

Files to download

Manual

Indexes

Index	Color	RAL
1546AL	ALUMINIUM	9006
1546GR	GRAPHITE	7016

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Before the installation, read the instructions attached to the luminaire. Due to the dynamic development of lighting technology, we provide additional information at the client's request. LED module replaceable by a person with appropriate qualifications, following applicable regulations. Condensation, which may occur in luminaires, is a natural phenomenon and does not deteriorate the quality of the luminaire