RENA 1552

Pobrano z mamadecor.pl

Rena 1552XX0014
23.07.2021 v.14.6
www.norlys.com

Type of luminaire

Type of lumianire	In-ground luminaire.
Photometric body	Uncovered light.
Characteristics of the luminaire	An orientation luminaire that can be driven on by vehicles with pneumatic tires. Luminaires should not be used on traffic lanes where they would be exposed to horizontal weight load as a result of sudden braking, acceleration, and change of direction. The light direction angle can be adjusted, up to a maximum of 10 degrees

General information

Materials	Powder painted aluminum cast. Front - stainless steel. Lens - safety glass, transparent. Silicone gasket. Nickel plated brass cable gland.
Mounting method	Fixing of the luminaire: 3 holes ø4,5mm on a diameter ø100mm every 120° connected to the assembly box, or to appropriately prepared hole in the wood (see manual). Other accessories sold separately
Terminal	The luminaire is equipped with a cable type 05RN8-F 3G1 with a length of 3m. To be connected in a properly selected installation box. The maximum load of the luminaire is 2000 kg. Note: on the glass surface in the middle work point, operating temperatures are in accordance with the standard 60598 (ambient temperature 15ºC)
Type of light source	LED Gu10 lamp
Net / gross weight of luminaire	1,01kg / 1,21kg
Box dimensions [cm]	15,6x15,6x19,4

Technical data

Light source wattage	max 6W
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class

It is possible to order the luminaire with the LED Gu10 lamp
type Philips Master LED ExpertColor 5,5W <=> 50W PAR16 Gu10 375lm / 800cd / 3000K / 36D (dimmable).
To the luminaire, in order to obtain light covered from above, a round diaphragm cover, can be mounted art.140xx0009

Accessories sold separately

143ZX0009	Power cord cover
145ZX0009	Hermetic 3-track box
146ZX0009	Hermetic 8-track box
46102506	LED Gu10 lamp

Recommended light sources

Osram LED Parathom max 6W <=> 50W PAR16 Gu10	Philips Master LED max 6W<=>50W PAR16 Gu10

Spare parts

06155000	Lens.
08155001	Gasket.

Files to download

Photometric LDT files	Photometric IES files
Manual	BIM ArchiCAD

Indexes

Index	Color	RAL
1552ST	STAINLESS STEEL	-

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Please read the manual before installing it. Due to the dynamic development of lighting technology, additional information is available upon request. LED modules must be replaced by a qualified person in accordance with applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not impair the quality of the luminaire