ARENDAL 1565

Pobrano z mamadecor.pl

Arendal 1565XX0012
23.07.2021 v.12.7
www.norlys.com

Type of luminaire

Type of lumianire	Bollard.
Photometric body	Uncovered light.
Characteristics of the luminaire	Modern design luminaire with a combination of decorative crystal lampshade and durable and stable casing

General information

Materials	Hot-dip galvanized and powder-coated steel. Lens - crystal glass, satin inside. Lens may change to light amber colour over time.
Mounting method	Fixing of the luminaire: 3 holes ø9mm with a diameter of ø65mm every 120°
Terminal	Connection terminals: max 3x4mm², possibility to connect luminaire in loop max 3x2,5mm². Round insulated cable with a diameter of max ø12,5mm.
Type of light source	E27 lamp
Net / gross weight of luminaire	9,11kg / 10,13kg
Box dimensions [cm]	61,5x18,5x18,5

Technical data

E27 lamp	QA55 / LED A55..60
Light source wattage	max 46W / LED 9W
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class

Possibility to order the luminaire with LED E27 Philips Master LEDbulb 806lm / 8,5W / 2700K (dimmable)

Accessories sold separately

205ZX0010	Concreting anchor
206GA0010	Ground anchor
206GA0S10	Anchoring support.
46999021	LED E27 lamp

Recommended light sources

Osram LED Parathom Classic E27	Philips Master LEDbulb / Ledbulb Classic E27
Osram ECO PRO Classic 46<=>60W E27	Philips ECO Classic 42<=>60W E27

Spare parts

915600229	Lens.

Files to download

Manual

Indexes

Index	Color	RAL
1565B	BLACK	9005
1565GA	GALVANIZED	-
1565GR	GRAPHITE	7016

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Please read the manual before installing it. Due to the dynamic development of lighting technology, additional information is available upon request. LED modules must be replaced by a qualified person in accordance with applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not impair the quality of the luminaire.