SANDVIK 1730

Pobrano z mamadecor.pl

Sandvik 1730XX0009
23.07.2021 v.09.14
www.norlys.com

Type of luminaire

Type of lumianire	Wall luminaire.
Photometric body	Double-sided light facing up and down.
Characteristics of the luminaire	Classic design ceiling luminaire. For lighting private areas and public spaces.

General information

Materials	Powder painted aluminum cast. Lens - safety glass, transparent. Silicone gasket. EPDM cable gland.
Mounting method	Fixing of the luminaire: 2 holes ømm, spacing mm.
Terminal	Connection terminals: max 3x2,5mm², possibility to connect luminaire in loop max 3x1,5mm². A round wire in the isolation with a diameter of ø7...10,5mm.
Type of light source	Gu10 lamp

Technical data

Light source wattage	2 x max 4W
Ta Rated temperature	+25°C

This product contains light sources of energy efficiency class

Recommended light sources

Osram LED Parathom Advanced / Pro max 4W PAR16 Gu10

Philips Master LED max 4W PAR16 Gu10

Files to download

Photometric LDT files

Photometric IES files

Manual

Indexes

Index	Color	RAL
1730AL	ALUMINIUM	9006
1730B	BLACK	9005
1730BC	BLACK/COPPER	-
1730GR	GRAPHITE	7016
1730W	WHITE	9003

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Please read the manual before installing. Due to the dynamic development of lighting technology, additional information is available upon request. LED module must be replaced by a qualified person in accordance with applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not impair the quality of the luminaire.