SANDVIK 1732

Pobrano z mamadecor.pl

Sandvik 1732XX0009
23.07.2021 v.09.35
www.norlys.com

Type of luminaire

Type of lumianire	Wall luminaire.
Characteristics of the luminaire	Classic design ceiling luminaire. For lighting private areas and public spaces.

General information

Materials	Powder painted aluminum cast. Lens - safety glass, transparent. Silicone gasket. EPDM cable gland.
Mounting method	Mounting of the luminaire: 2 holes ø 4.5mm, spacing 37mm x 97.5mm
Terminal	Connection terminals: max 3x2.5mm², Possibility of connecting the luminaire in loops max 3x1.5mm², Round insulated cable with a diameter of ø7 ... 10.5mm
Type of light source	LED module AC integrated
Light control	Phase-dimming (TRIAC).
Net / gross weight of luminaire	1,47kg / 1,58kg

Technical data

2 LED modules	Lumens EDC 38C 8W xxx 230V A Ver.1.2 (Datasheet)
External control	Dimmers Lumens LED AC (User manual)
Light source wattage	2x8W
Luminaire wattage	16W
Lamp luminous flux	1512lm
Luminaire luminous flux	1126lm
Efficiency of the luminaire	70,4lm/W
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	>50 000h
LED photobiological threat	RG0 or RG1
Power Factor luminaire	PF>0,98
THD factor	< 20%
Ta Rated temperature	+25°C
Max ambient temperature	-35...+35°C

This product contains light sources of energy efficiency class

Inrush current	70mA / 60ms

Spare parts

4699102301	LED module.
ZS1732zx0009	Service set.

Files to download

Photometric LDT files	Photometric IES files
Manual	

Indexes

Index	Color	RAL
1732AL	ALUMINIUM	9006
1732B	BLACK	9005
1732GR	GRAPHITE	7016
1732W	WHITE	9003

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Before the installation, read the instructions attached to the luminaire. Due to the dynamic development of lighting technology, we provide additional information on customer's requests. LED module replaceable by a person with appropriate qualifications, following applicable regulations. Condensation, which may occur in luminaires, is a natural phenomenon and does not deteriorate the quality of the luminaire