NAMSOS 1933

Pobrano z mamadecor.pl

Namsos 1933XX0011
23.07.2021 v.11.7
www.norlys.com

Type of luminaire

Type of lumianire	Recessed wall luminaire.
Photometric body	Covered light facing down.
Characteristics of the luminaire	The luminaire is adapted to illuminate stairs, steps, staircases, communication pathways and other applications

General information

Materials	Front - hot-dip galvanized steel. Body - powder painted aluminum cast Lens - safety glass, satin. Silicone gasket. EPDM cable gland.
Mounting method	Fixing the luminaire: embedded in the wall - hole 258x112x115, fixing in a sandwich wall - hole 235x96x82
Terminal	Connection terminals: max 3x2.5mm², Possibility to connect the luminaire in loops, max 3x1.5mm². Round insulated cable with a diameter of ø7 ... 10.5mm
Type of light source	LED module, power supply
Light control	Trailing edge dimming
Net / gross weight of luminaire	1,41kg / 1,6kg
Box dimensions [cm]	27x14x13

Technical data

LED module	Philips Strip OC 0.5ft 550lm 8xx FC HV5 (Datasheet)
Driver	Philips Xitanium 7W 0,35A 20V TE SC 230V (Datasheet)
Light source wattage	3,9W
Luminaire wattage	5,2W
Lamp luminous flux	653lm
Luminaire luminous flux	295lm
Light source efficiency	167,4lm/W
Efficiency of the luminaire	56,7lm/W
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	>70 000h
Power Factor luminaire	PF > 0,96
THD factor	20 %
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class

Inrush current	1A/15,2µs

Spare parts

ZS1933zx0011	LED module.

Files to download

Photometric LDT files	Photometric IES files
Manual	

Indexes

Index	Color	RAL
1933GA	GALVANIZED	-

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Before the installation, read the instructions attached to the luminaire. Due to the dynamic development of lighting technology, we provide additional information at the client's request. LED module replaceable by a person with appropriate qualifications, following applicable regulations. Condensation, which may occur in luminaires, is a natural phenomenon and does not deteriorate the quality of the luminaire