LOFOTEN 1941

Pobrano z mamadecor.pl

Lofoten 1941XX0011
23.07.2021 v.11.4
www.norlys.com

Type of luminaire

Type of lumianire	Bollard.
Photometric body	Uncovered light, partly covered from the top.
Characteristics of the luminaire	Classic design luminaire for general use. For lighting terraces, entrances, arbors and other architectural concepts.

General information

Materials	Galvanized and powder coated steel. Lens - safety glass, transparent. Silicone gasket. EPDM cable gland.
Mounting method	Fixing the luminaire: 4 holes ø5,8mm spacing 70x70mm, for mounting on a wall, platform and other construction.
Terminal	Connection terminals: max 2x2,5mm², possibility to connect luminaire in max 2x1,5mm². A round wire in the isolation with a diameter of ø7...10,5mm.
Type of light source	E27 lamp
Net / gross weight of luminaire	2,89kg / 3,27kg
Box dimensions [cm]	25x25x29

Technical data

Light source wattage	MAX 57W / LED 11W
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class

Possibility to order the luminaire with LED E27 Philips Master LEDbulb 806lm / 8,5W / 2700K (dimmable).

Accessories sold separately

46999021	LED E27 lamp.

Recommended light sources

Osram LED Parathom Classic / Retrofit 10...12<=>75W E27	Philips ECO Classic 53<=>75W E27
Osram LED Parathom Classic / Retrofit E27	Philips Master LEDbulb / Classic / CorePro E27

Files to download

Manual

Indexes

Index	Color	RAL
1941B	BLACK	9005

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Please read the manual before installing. Due to the dynamic development of lighting technology, additional information is available upon request. LED module must be replaced by a qualified person in accordance with applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not impair the quality of the luminaire.