Pobrano z mamadecor.pl

STOCKHOLM Heavy duty galvanized steel or galvanized and powder coated bollard with opal or clear polycarbonate lens.

Art	Watt	Class	Type of light source:	Luminous □ux	Colour temperature	Lifetime (L70/B50)	EEI	Lens	Height (cm)	Dimmable
299	-	II	E27	-	-	-	A+..D	Opal polycarbonate	28cm	-
1269	8,5W	II	LED E27	-	2700K	25 000h	A+	Opal polycarbonate	28cm	Dim. Triac
1268	10W	I	LED	294 lm	3000K	50 000h	A+	Opal polycarbonate	28cm	Dim. Triac
289	-	II	E27	-	-	-	A+..D	Opal polycarbonate	49cm	-
298	-	II	E27	-	-	-	A+..D	Clear polycarbonate	49cm	-
1469	8,5W	II	LED E27	294 lm	2700K	25 000h	A+	Opal polycarbonate	49cm	Dim. Triac
1260	10W	I	LED	294 lm	3000K	50 000h	A+	Opal polycarbonate	49cm	Dim. Triac

Accessories for Stockholm		
205	Concreting anchor	p. 114
206	Anchoring support	p. 114

Art. 299
Art. 1269
Art. 1268

Art. 289
Art. 298
Art. 1469
Art. 1260

Art. 1269, i 1469: 8,5W LED E27 included, 806 lm, 2700K, 25000h, dimmable, EEI: A+

*** Stockholm with 4000K** available by request, contact your supplier.