STOCKHOLM 220

Pobrano z mamadecor.pl

Stockholm 220XX0010
23.07.2021 v.10.2
www.norlys.com

Type of luminaire

Type of lumianire	Wall luminaire.
Photometric body	Diffused, uncovered light.
Characteristics of the luminaire	Plafon type luminaire in scandinavian design. For lighting gardens, private areas and public spaces.

General information

Materials	Base - powder painted aluminum cast. Hot-dip galvanized and powder-coated steel. Lens - milky polycarbonate, UV stabilized. Silicone gasket.
Mounting method	Fixing of the luminaire: 2 holes ø5mm, spacing 80x80mm.
Terminal	Connection terminals: max 3x2,5mm², possibility to connect luminaire in loop max 3x2,5mm². A round wire in the isolation with a diameter of ø7...10,5mm.
Type of light source	E27 lamp
Net / gross weight of luminaire	2,5kg / 2,7kg
Box dimensions [cm]	22x15,5x25

Technical data

E27 lamp	QA55 / LED A55..60
Light source wattage	MAX 46W / LED 9W
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class

Possibility to order the luminaire with LED E27 Philips Master LEDbulb 806lm / 8,5W / 2700K (dimmable).

Recommended light sources

Osram LED Parathom Classic E27	Philips Master LEDbulb / Ledbulb Classic E27
Osram ECO PRO Classic 46<=>60W E27	Philips ECO Classic 42<=>60W E27

Spare parts

06220000	Lens.
08550005	Gasket.

Files to download

Manual

Indexes

Index	Color	RAL
220B	BLACK	9005
220GA	GALVANIZED	-

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Please read the manual before installing. Due to the dynamic development of lighting technology, additional information is available upon request. LED module must be replaced by a qualified person in accordance with applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not impair the quality of the luminaire.