

LUND 275

Pobrano z mamadecor.pl

Lund 275XX0309
23.07.2021 v.09.1
www.norlys.com





Type of luminaire

Type of lumianire	Accessories
Photometric body	Uncovered light.
Characteristics of the luminaire	Scandinavian design luminaire, mounted on a telescopic lighting pole. Adjustable height 1700..2300mm. For lighting gardens, terraces and other architectural concepts.

General information

Materials	Hot-dip galvanized steel. Powder painted steel. Lens - clear polycarbonate, UV stabilized.
Mounting method	Fixing of the luminaire: 3 holes ø10,5mm, on a daimeter ø207mm every 120°. Set contains: Art. 2020 - luminaire, Art. 3009 - steel, hot-dip galvanized lighting pole, Art. 3011 - aluminum, powder coated lighting pole in black colour. Other accessories need to be purchased separately.
Terminal	Connection terminal: max 3x4mm² cable, possibility to connect luminaire in loop max 3x1,5mm². A round wire in the isolation with a diameter of max ø12,5mm.
Type of light source	E27 lamp

Technical data

E27 lamp	QA55 / LED A55..60
Light source wattage	2 x max 57W / LED 9W
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class

Possibility to order the luminaire with LED E27 Philips Master LEDbulb 806lm / 8,5W / 2700K (dimmable).

Accessories sold separately

405ZX0009	Concreting anchor.
406ZX0009	Ground anchor.

Recommended light sources

Osram ECO PRO Classic 57<=>75W E27	Philips ECO Classic 53<=>75W E27
Osram LED Parathom Classic / Retrofit E27	Philips Master LEDbulb / Classic / CorePro E27

Spare parts

06240000	Lens.

Files to download

Manual

Indexes

Index	Color	RAL
275B	BLACK	9005
275GA	GALVANIZED	-

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Please read the manual before installing. Due to the dynamic development of lighting technology, additional information is available upon request. LED module must be replaced by a qualified person in accordance with applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not impair the quality of the luminaire.