STOCKHOLM 281

Pobrano z mamadecor.pl

Stockholm 281XX0309
23.07.2021 v.09.3
www.norlys.com

Type of luminaire

Type of lumianire	Accessories
Photometric body	Uncovered light.
Characteristics of the luminaire	Pole top luminaire in scandinavian design. For installation on a lighting pole with adjustable height 1510...2480mm. For lighting gardens, parks, and any other architectural concepts.

General information

Materials	Hot-dip galvanized steel. Powder painted steel. Lens - transparent plastic PMMA.
Mounting method	Fixing of the luminaire: 3 holes Ø10,5 on a diameter Ø270mm every 120°. Set contains: art.2017- luminaire art. 3009/3011- lighting pole Other accessories need to be purchased separately.
Terminal	Connection terminals: max 4x2,5mm², possibility to connect luminaire in loop max 4x2,5mm². A round wire in the isolation on diameter ø6...12,5mm.
Type of light source	E27 lamp

Technical data

E27 lamp	QA55 / LED A55..60
Light source wattage	max 77W / LED 9W
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class

Recommended light sources

Philips Master LEDbulb / Classic / CorePro E27	Osram ECO PRO Classic 77<=>100W E27
Philips ECO Classic 70<=>100W E27	Philips Master LEDbulb / LEDbulb Classic E27

Spare parts

06281002	Lens.
08281001	Gasket.

Files to download

Photometric LDT files	Photometric IES files
Manual	

Indexes

Index	Color	RAL
281B	BLACK	9005
281GA	GALVANIZED	-

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Please read the manual before installing. Due to the dynamic development of lighting technology, additional information is available upon request. LED module must be replaced by a qualified person in accordance with applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not impair the quality of the luminaire.