STOCKHOLM 285

Pobrano z mamadecor.pl

Stockholm 285XX0010
23.07.2021 v.10.1
www.norlys.com

Type of luminaire

Type of lumianire	Bollard.
Photometric body	Uncovered light.
Characteristics of the luminaire	Scandinavian design luminaire for general use. For lighting gardens, terraces and any other architectural concepts.

General information

Materials	Hot-dip galvanized and powder-coated steel. Lens - transparent plastic PMMA.
Mounting method	Fixing of the luminaire: using attached anchor, 3 holes ø7mm on a diameter ø120mm every 120°.
Terminal	Connection terminals: max 2x2,5mm². A round wire in the isolation with a diameter of max ø12mm.
Type of light source	E27 lamp

Technical data

E27 lamp	QA55 / LED A55..60
Light source wattage	max 46W / LED 9W

This product contains light source of energy efficiency class

Recommended light sources

Osram LED Parathom Classic E27	Philips Master LEDbulb / Ledbulb Classic E27
Osram ECO PRO Classic 46<=>60W E27	Philips ECO Classic 42<=>60W E27

Spare parts

06280007	Lens.
08280014	Gasket.

Files to download

Photometric LDT files	Photometric IES files
Manual	

Indexes

Index	Color	RAL
285B	BLACK	9005

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Please read the manual before installing. Due to the dynamic development of lighting technology, additional information is available upon request. LED module must be replaced by a qualified person in accordance with applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not impair the quality of the luminaire.