STOCKHOLM 286

Pobrano z mamadecor.pl

Stockholm 286XX0010
23.07.2021 v.10.2
www.norlys.com

Type of luminaire

Type of lumianire	Wall luminaire.
Photometric body	Uncovered light.
Characteristics of the luminaire	Scandinavian design, wall-mounted luminaire for general use. Possibility to install on corners of architectural objects.

General information

Materials	Hot-dip galvanized steel. Powder painted steel. Lens - transparent plastic PMMA. Silicone gasket. EPDM cable gland.
Terminal	Connection terminals: max 2x2,5mm². A round wire in the isolation with a diameter of ø7...10,5mm.
Type of light source	E27 lamp
Net / gross weight of luminaire	3,58kg / 4,13kg
Box dimensions [cm]	36x21,5x39,5

Technical data

E27 lamp	QA55 / LED A55..60
Light source wattage	max 77W / LED 9W
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class

Possibility to order luminaire with LED E27 light source type Philips Master LEDbulb 806lm/8,5W/2700K (dimmable).

Accessories sold separately

153XX0009	Mounting corner.
159XX0009	Luminaire mounting distance
46999021	LED E27 lamp.

Recommended light sources

Osram LED Parathom Classic / Retrofit 10...12<=>75W E27	Philips CorePro LEDbulb 10...12<=>75W E27
Osram ECO PRO Classic 57<=>75W E27	Philips ECO Classic 53<=>75W E27
Philips Master LEDbulb 10...12W <=> 75W E27	

Spare parts

06281002	Lens.
08281001	Gasket.

Files to download

Photometric LDT files	Photometric IES files
Manual	

Indexes

Index	Color	RAL
286B	BLACK	9005

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Please read the manual before installing. Due to the dynamic development of lighting technology, additional information is available upon request. LED module must be replaced by a qualified person in accordance with applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not impair the quality of the luminaire.