

MODENA 301

Pobrano z mamadecor.pl

Modena 301XX0309
23.07.2021 v.09.1
www.norlys.com





Type of luminaire

Type of lumianire	Accessories
Photometric body	Uncovered light.
Characteristics of the luminaire	Classic design luminaire, mounted on a telescopic lighting pole. Adjustable height 1930..2830mm. For lighting gardens, terraces and other architectural concepts.

General information

Materials	Powder painted aluminum cast. Lens - clear polycarbonate, UV stabilized. EPDM cable gland.
Mounting method	Fixing of the luminaire: 3 holes ø10,5mm, on a daimeter ø240mm every 120°. Set contains: Art. 3012 - luminaire, Art. 3010 - lightning pole. Other accessories need to be purchased separately.
Terminal	Connection terminal: max. 4x2,5mm², possibility to connect luminaire in loop max 4x2,5mm². A round wire in the isolation with a diameter of max ø7...12,5mm.
Type of light source	E27 lamp
Net / gross weight of luminaire	9,78kg / 12,82kg

Technical data

E27 lamp	QA55 / LED A55..60
Light source wattage	max 77W / LED 9W

This product contains light source of energy efficiency class

Accessories sold separately

305ZX0009	Concreting anchor.
306ZX0009	Ground anchor.

Recommended light sources

Osram LED Parathom Classic / Retrofit E27	Philips Master LEDbulb / Classic / CorePro E27
Osram ECO PRO Classic 77<=>100W E27	Philips ECO Classic 70<=>100W E27

Spare parts

06380004	Lens.

Files to download

Manual

Indexes

Index	Color	RAL
301B	BLACK	9005
301W	WHITE	9003

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Please read the manual before installing. Due to the dynamic development of lighting technology, additional information is available upon request. LED module must be replaced by a qualified person in accordance with applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not impair the quality of the luminaire.