MODENA 304

Pobrano z mamadecor.pl

Modena 304XX0010
23.07.2021 v.10.2
www.norlys.com

Type of luminaire

Type of lumianire	Bollard.
Photometric body	Uncovered light with rotationally symmetrical light distribution.
Characteristics of the luminaire	Classic design luminaire. For lighting gardens and other private areas and public spaces.

General information

Materials	Powder painted aluminum cast. Lens - clear polycarbonate, UV stabilized. EPDM cable gland.
Mounting method	Fixing of the luminaire: 2 holes ø5,5mm, spacing 90mm.
Terminal	Connection terminals: max 2x2,5mm², possibility to connect luminaire in loop max 2x1,5mm². A round wire in the isolation with a diameter of ø7...10,5mm.
Type of light source	E27 lamp
Net / gross weight of luminaire	2,56kg / 3,41kg
Box dimensions [cm]	24,5x23x82

Technical data

E27 lamp	QA55 / LED A55..60
Light source wattage	max 77W / LED 9W
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class

Accessories sold separately

307ZX0009	Concreting anchor.
46999021	LED E27 lamp.

Recommended light sources

Osram LED Parathom Classic / Retrofit E27	Philips Master LEDbulb / Classic / CorePro E27
Osram ECO PRO Classic 77<=>100W E27	Philips ECO Classic 70<=>100W E27

Spare parts

06350004	Lens.

Files to download

Manual

Indexes

Index	Color	RAL
304B	BLACK	9005
304W	WHITE	9003

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Please read the manual before installing. Due to the dynamic development of lighting technology, additional information is available upon request. LED module must be replaced by a qualified person in accordance with applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not impair the quality of the luminaire.