BOLOGNA 362

Pobrano z mamadecor.pl

Type of luminaire

Type of lumianire	Pole luminaire.
Photometric body	Uncovered light.
Characteristics of the luminaire	Classic design luminaire, mounted on a telescopic lighting pole. Adjustable height 1650..2540mm. For lighting gardens, terraces and other architectural concepts.

General information

Materials	Powder painted aluminum cast. Lens - transparent plastic PMMA. Silicone gasket.
Mounting method	Fixing of the luminaire: 3 holes ø10,5mm, on a daimeter ø240mm every 120°. Set contains: art. 3025 - luminaire. Art. 3040 - reduction. Art. 3010 - lightning pole. Other accessories must be ordered separately.
Terminal	Connection terminal: max. 4x2,5mm² cable, possibility to connect luminaire in loop max 4x2,5mm². A round wire in the isolation with a diameter of max ø6...12,5mm.
Type of light source	E27 lamp
Net / gross weight of luminaire	9,91kg / 12,93kg
Side area of luminaire	0,12m^2

Technical data

E27 lamp	QA55 / LED A55..60
Light source wattage	2 x MAX 46W / LED 9W
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class

Possibility to order the luminaire with LED E27 Philips Master LEDbulb 806lm / 8,5W / 2700K (dimmable).

Accessories sold separately

108GA0009	Anchoring support.
305ZX0009	Concreting anchor.
306ZX0009	Ground anchor.
46999021	LED E27 lamp.

Recommended light sources

Osram ECO PRO Classic 46<=>60W E27	Philips ECO Classic 42<=>60W E27
Osram LED Parathom Classic / Retrofit E27	Philips Master LEDbulb / Classic / CorePro E27

Spare parts

06360008	Lens.

Files to download

Manual

Indexes

Index	Color	RAL
362B	BLACK	9005
362W	WHITE	9003

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Please read the manual before installing. Due to the dynamic development of lighting technology, additional information is available upon request. LED module must be replaced by a qualified person in accordance with applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not impair the quality of the luminaire.