HALMSTAD 5022

Pobrano z mamadecor.pl

Halmstad 5022XX0012
23.07.2021 v.12.5
www.norlys.com

Type of luminaire

Type of lumianire	Bollard.
Photometric body	Uncovered, diffused light with rotationally symmetrical light distribution.
Characteristics of the luminaire	A bollard luminaire with a stable and durable structure. For lighting private areas and public areas

General information

Materials	Hot-dip galvanized steel. Lens - plastic PMMA in milky color. Silicone gasket.
Mounting method	Mounting of the luminaire: 3 holes ø9mm on a diameter of ø65mm every 120 °. Other accessories must be purchased separately
Terminal	Connection terminals: max 3x4mm², possibility to connect the luminaire in loops max 3x2.5mm². Round insulated cable with a diameter max. of ø12.5mm
Type of light source	LED module AC integrated
Light control	Phase-dimming (TRIAC).
Net / gross weight of luminaire	13,35kg / 15,02kg
Box dimensions [cm]	15x15x91

Technical data

LED module	Lumens EDC 47C 10W xxx 230V A Ver.1.2 (Datasheet)
External control	Dimmers Lumens LED AC (User manual)
Light source wattage	10W
Luminaire wattage	10W
Lamp luminous flux	1164lm
Light source efficiency	116,4lm/W
Color temperature	4000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	50 000h
THD factor	< 20%
Ta Rated temperature	+25°C
Max ambient temperature	-35...+25°C

This product contains light source of energy efficiency class

Optional version, for a production date, please contact with a Sales Department of Norlys Sp. z o.o

Inrush current	43mA / 60ms

Accessories sold separately

205ZX0010	Concreting anchor
206GA0010	Ground anchor

Spare parts

06295000	Lens.
08295000	Gasket.
ZS5022zx0012	Service set.

Files to download

Manual BIM ArchiCAD

Indexes

Index	Color	RAL
5022B	BLACK	9005
5022GA	GALVANIZED	-
5022GR	GRAPHITE	7016

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Before the installation, read the instructions attached to the luminaire. Due to the dynamic development of lighting technology, we provide additional information at the client's request. LED module replaceable by a person with appropriate qualifications, following applicable regulations. Condensation, which may occur in luminaires, is a natural phenomenon and does not affect the quality of the luminaire