NORDKAPP 5026

Pobrano z mamadecor.pl

Nordkapp 5026XX0012
23.07.2021 v.12.3
www.norlys.com

Type of luminaire

Type of lumianire	Wall luminaire.
Photometric body	Diffused, uncovered light.
Characteristics of the luminaire	Modern design plafon type luminaire. For lighting private areas and public spaces.

General information

Materials	Powder painted aluminum cast. Lens - milky polycarbonate, UV stabilized. Silicone gasket. EPDM cable gland.
Mounting method	Fixing of the luminaire: 2 holes ø5mm, spacing 164x242mm.
Terminal	Connection terminals: max 3x2,5mm², possibility to connect luminaire in loop max 3x1,5mm². A round wire in the isolation with a diameter ø7...10,5mm.
Type of light source	LED module AC integrated
Light control	Phase-dimming (TRIAC).
Net / gross weight of luminaire	2,8kg / 3,1kg
Box dimensions [cm]	35x27x9,5

Technical data

LED module	LUMENS LED DLM90C/10W/840/230V/A
Light source wattage	10W
Luminaire wattage	10W
Lamp luminous flux	1100lm
Light source efficiency	110lm/W
Color temperature	4000K
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	50 000h
Power Factor luminaire	PF >0,90
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class

Inrush current	150mA/500µs

Spare parts

06524002	Lens.
08525000	Gasket.
46999401	LED module.

Files to download

Photometric LDT files	Photometric IES files
Manual	

Indexes

Index	Color	RAL
5026AL	ALUMINIUM	9006
5026GR	GRAPHITE	7016
5026W	WHITE	9003

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Please read the manual before installing. Due to the dynamic development of lighting technology, additional information is available upon request. LED module must be replaced by a qualified person in accordance with applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not impair the quality of the luminaire.