ASKER 5124

Pobrano z mamadecor.pl

Asker 5124XX0010
23.07.2021 v.10.9
www.norlys.com

Type of luminaire

Type of lumianire	Bollard.
Photometric body	Covered light facing down.
Characteristics of the luminaire	Luminaire with contemporary design. For lighting gardens and other private land and public areas

General information

Materials	Powder painted aluminum cast. Lens - transparent polycarbonate with structure, UV stabilized. Silicone gasket.
Mounting method	Fixing of the luminaire: 4 holes ø 8mm, spacing 18x50mm
Terminal	Connection terminals: max 3x2,5mm², Possibility to connect luminaire in loop max 3x1,5mm². Round insulated cable with a diameter of max ø12,5mm.
Type of light source	LED module AC integrated
Light control	Non-dimmable luminaire
Net / gross weight of luminaire	4,01kg / 4,36kg
Box dimensions [cm]	105,7x10,7x5

Technical data

LED module	Philips Fortimo LED DLM ES 1100 lm G2
Light source wattage	9,5W
Luminaire wattage	9.5W
Lamp luminous flux	1150lm
Luminaire luminous flux	640lm
Light source efficiency	121,1lm/W
Efficiency of the luminaire	67,4lm/W
ULOR	0%
Color temperature	4000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	50 000h
Power Factor luminaire	PF>0,97
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class

Accessories sold separately

1907ZX0009	Concreting anchor.
1908GA0009	Ground anchor.
3081XX0009	Handle for mounting to the base

Spare parts

06131100	Lens.
08131100	Gasket.
46999756	LED module.

Files to download

Photometric LDT files	Photometric IES files
Manual	BIM Revit
BIM ArchiCAD	

Indexes

Index	Color	RAL
5124AL	ALUMINIUM	9006
5124B	BLACK	9005
5124GR	GRAPHITE	7016

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Please read the manual before installing. Due to the dynamic development of lighting technology, additional information is available upon request. LED module must be replaced by a qualified person following applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not impair the quality of the luminaire.