ASKER POLE 5127

Pobrano z mamadecor.pl

Asker pole 5127XX0010
23.07.2021 v.10.7
www.norlys.com

Type of luminaire

Photometric body	Single-sided, symmetric light facing down.
Characteristics of the luminaire	For lighting private areas and other concepts architectural

General information

Materials	Extruded aluminum profile, powder coated. Lens - transparent polycarbonate with structure, UV stabilized. Silicone gasket.
Mounting method	Mounting of the luminaire: 4 holes ø12mm, spacing 200x200mm Art. 1363: 1 section pillar luminaire, Other accessories must be purchased separately
Terminal	Connection terminals: max 3x2.5mm², Possibility of connecting the luminaire in loops of max 3x2.5mm². Round insulated cable with a maximum diameter of ø12.5mm
Type of light source	LED module AC integrated
Light control	Phase-dimming (TRIAC).
Net / gross weight of luminaire	11kg / 17,05kg
Box dimensions [cm]	26x240x53
Side area of luminaire	0,258m^2

Technical data

2 LED modules	Lumens LNM/280X30/9W/840/230V
Light source wattage	18W
Luminaire wattage	18W
Lamp luminous flux	1778lm
Luminaire luminous flux	1100lm
Light source efficiency	98,8lm/W
Efficiency of the luminaire	61,1lm/W
ULOR	0%
Color temperature	4000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	50 000h
Power Factor luminaire	PF 0,99
Ta Rated temperature	+25°C

This product contains light sources of energy efficiency class

Inrush current	108,8mA/500µs

Accessories sold separately

116ZX0009	Concreting anchor (anchor L190mm)
117GA0009	Ground anchor
118GA0009	Anchoring support
119ZX0009	Concreting anchor (anchor L700mm)
7666ZX0009	Connection box with fuse 5x20mm

Spare parts

06136000	Lens.
08136000	Gasket.
46999389	LED module.

Files to download

Photometric LDT files	Photometric IES files
Manual	BIM Revit
BIM ArchiCAD	

Indexes

Index	Color	RAL
5127AL	ALUMINIUM	9006
5127B	BLACK	9005
5127GR	GRAPHITE	7016

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Before the installation, read the instructions attached to the luminaire. Due to the dynamic development of lighting technology, we provide additional information at the client's request. LED module replaceable by a person with appropriate qualifications, following applicable regulations. Condensation, which may occur in luminaires, is a natural phenomenon and does not deteriorate the quality of the luminaire