HALDEN 517

Pobrano z mamadecor.pl

Halden 517XX0013
23.07.2021 v.13.4
www.norlys.com

Type of luminaire

Type of lumianire	Wall luminaire.
Photometric body	Single-sided light facing down.
Characteristics of the luminaire	Luminaire with a wide range of applications for example for illumination of walls and facade surfaces or any other architectural concepts.

General information

Materials	Powder painted aluminum cast. Lens - transparent polycarbonate with structure, UV stabilized. Silicone gasket. EPDM cable gland.
Mounting method	Fixing of the luminaire: mounting plate with 2 adjust holes 7x10mm, spacing 100mm.
Terminal	Connection terminals: max 3x2,5mm², possibility to connect luminaire in max 3x1,5mm². A round wire in the isolation with a diameter of ø7...10,5mm.
Type of light source	LED module, power supply
Light control	Trailing edge dimming
Net / gross weight of luminaire	2kg / 2kg
Box dimensions [cm]	34x17x16,5

Technical data

LED module	Philips LED SLM C 830 1203 L09 1619 G7
Light source wattage	6,7W
Luminaire wattage	8,5W
Lamp luminous flux	1059lm
Luminaire luminous flux	682lm
Light source efficiency	158,1lm/W
Efficiency of the luminaire	80,2lm/W
ULOR	0%
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	>50 000h
Power Factor luminaire	PF 0,90
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class

Inrush current	1,65A / 16,5µs

Maximum number of luminaires of this type per MCB:

B 10A: 160, **B 16A**: 254, **C 10A**: 264, **C 16A**: 431

Spare parts

06120004	Lens.
46999610	Power supply.
46999691	LED module.
ZS517ZX0013	Service set.

Files to download

Photometric LDT files	Photometric IES files
Manual	

Indexes

Index	Color	RAL
517AL	ALUMINIUM	9006
517GR	GRAPHITE	7016
517W	WHITE	9003

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Please read the manual before installing. Due to the dynamic development of lighting technology, additional information is available upon request. LED module must be replaced by a qualified person in accordance with applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not impair the quality of the luminaire.