RONDANE 539

Pobrano z mamadecor.pl

Rondane 539XX0010
23.07.2021 v.10.3
www.norlys.com

Type of luminaire

Type of lumianire	Wall/ceiling luminaire.
Photometric body	Diffused, uncovered light.
Characteristics of the luminaire	Modern design plafon type luminaire

General information

Materials	Powder painted aluminum cast. Lens - milky polycarbonate, UV stabilized. Silicone gasket. EPDM cable gland.
Mounting method	Mounting of the luminaire: 2 holes ø5mm, spacing 165x95mm
Terminal	Connection terminals: max 3x2.5mm², Possibility to connect the luminaire in loops, max 3x1.5mm², Round insulated cable with a diameter of ø7 ... 10.5mm
Type of light source	LED module AC integrated
Light control	Non-dimmable luminaire
Net / gross weight of luminaire	1,56kg / 1,84kg
Box dimensions [cm]	26,5x26,5x11

Technical data

LED module	Philips Fortimo LED DLM ES 2000lm
Light source wattage	17,5W
Luminaire wattage	17,5W
Lamp luminous flux	1950lm
Luminaire luminous flux	732lm
Light source efficiency	111,4lm/W
Efficiency of the luminaire	41,8lm/W
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	50 000h
Power Factor luminaire	PF > 0,9
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class

Inrush current	3,01A/32,66µs

Maximum number of luminaires of this type per MCB:

B 10A: 81, **B 16A**: 130, **C 10A**: 135, **C 16A**: 221

Spare parts

06520002	Lens.
08525000	Gasket.
46999751	LED module.

Files to download

Photometric LDT files	Photometric IES files
Manual	

Indexes

Index	Color	RAL
539AL	ALUMINIUM	9006
539GR	GRAPHITE	7016

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no



Before the installation, read the instructions attached to the luminaire. Due to the dynamic development of lighting technology, we provide additional information at the client's request. LED module replaceable by a person with appropriate qualifications, following applicable regulations. Condensation, which may occur in luminaires, is a natural phenomenon and does not deteriorate the quality of the luminaire